






4 čelistní samostředící sklíčidla

2 sady čelistí





Specifikace

Označení výrobku	D	d1	d2	d3	L	L1	h	Závit	Rozsah upnutí		Hmotnost (kg)	Objednací kód
									vnější průměr rozsah	vnitřní průměr rozsah		
VPS-6A	165	130	145	45	94	65	5	3-M8	Ø4-Ø165	Ø55-Ø150	9.3	5002-050
VPS-8A	200	165	180	65	109	75	5	3-M10	Ø4-Ø200	Ø65-Ø200	16.6	5002-052
VPS-10A	250	206	226	80	120	80	5	3-M12	Ø6-Ø250	Ø90-Ø250	28	5002-053
VPS-12A	315	260	285	100	147.5	90	6	3-M16	Ø10-Ø315	Ø100-Ø315	54	5002-054



4 čelistní samostředící sklíčidla

Vyměnitelné vrchní čelisti



Specifikace

Označení výrobku	D	d1	d2	d3	L	L1	h	Závit	Rozsah upnutí		Hmotnost (kg)	Objednací kód
									vnější průměr rozsah	vnitřní průměr rozsah		
VPS-6AK	165	130	145	45	109	65	5	3-M8	Ø4-Ø165	Ø55-Ø150	9.5	5002-055
VPS-8AK	200	165	180	65	122	75	5	3-M10	Ø4-Ø200	Ø65-Ø200	14.8	5002-057
VPS-10AK	250	206	226	80	136	80	5	3-M12	Ø6-Ø250	Ø90-Ø250	24.7	5002-058
VPS-12AK	315	260	285	100	156.5	90	6	3-M16	Ø10-Ø315	Ø100-Ø315	45.7	5002-059





3 čelistní výkonný typ samostředícího sklíčidla

NEW



Ød2	
D1-4	143.06
D1-5	104.8
D1-6	133.4
D1-8	171.4
D1-11	235.0



Označení výrobku	D	Montážní typ	d1	d2	d3	d4	L	H1	h	Závit	Hmotnost (kg)	Objednací kód
VSKC-6A	160	D5	40	104.8	146	82.563	12	73	15	6-M12x1.0P	10	5002-111
VSKC-8A	200	D6	50	133.4	181	106.375	13	86	16	6-M16x1.5P	17	5002-112
VSKC-10A	250	D6	70	133.4	181	106.375	13	98	16	6-M16x1.5P	32	5002-113
VSKC-12A	315	D6	100	133.4	181	106.375	13	103.5	16	6-M16x1.5P	49	5002-114